Caltrans	JENS COUNTY	ROUTE	KILOMETER POST TOTAL PROJECT	SHEE!	TOTAL
etric	REGISTERED CIVI	L ENGINEER	181 W.	Greg Edwards	121
	PLANS APPROVAL	DATE	11 a pro	C36386	-/ 5//
	The State of Califor agents shall not be r or completeness of sheet.	responsible fo	ficers or	6-30-04 CIVIL F CAL IFORM	/ 4//
	Caltrans now has a	web site! To a	net to the web site, on to: h	to-//www	dot ca gov

T	ABLE I-	DELINEATORS			
TYPE	RETROREFLECTIVE SHEETING				
	FRONT	BACK			
E	White	White (See Note I)			
F	White	None			
G	Yellow	None			
1	Yellow	Yellow (See Note I)			
J	Red	None			

NOTES

- 1. The retroreflective sheeting used on the back of delineator shall be a minimum size of 75 mm x 75 mm.
- 2. The type of delineator to be installed will be designated on the plans.
- 3. All barricade stripes shall be retroreflective.
- 4. See Standard Plan A738 for Metal Post Details.
- 5. Unless shown otherwise on the plans, or as directed by the Engineer, the color of the retroreflective sheeting for permanent channelizers shall conform to the color of the pavement markings it supplements.
- 6. Except, Class 1 (Flexible Post) temporary delineators and temporary channelizers in work zones shall be orange with white retroreflective DOST

STATE OF CALIFORNIA DEPARTMENT OF TRANSPORTATION

DELINEATORS, CHANNELIZERS AND BARRICADES

NO SCALE

ALL DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SHOWN

A73C


2004

S

td

PLAN

A73C



BARRICADES (See Note 3)

TYPE II BARRICADE

200 to 300 \$

Only face of rails shown. Barricade construction materials and supports as specified in the specifications.

TABLE 2 - BARRICADES					
BARRICADE	TYPE I	TYPE II	TYPE III		
Width of Rail	2 <mark>00 Min-300 Max *</mark>	200 Min-300 Max *	200 Min-300 Max *		
Length of Rail	O.6 m Min	0.6 m Min	1.2 m Min		
Width of Stripes * *	<mark>- 150</mark> -	150	150		
Height	0.9 m Min	0.9 m Min	I.5 m Min		
Number of Retroreflective Rail Faces	2 (one each direction)	4 (two each direction)	3 if facing traffic in one direction 6 if facing traffic in two direction		

For the wooden option dimensions are nominal lumber dimensions. * * For rails less than 0.9 m long, 100 mm wide stripes shall be used.

NOTE A

200 to 300 \$

TYPE III BARRICADE

Barricades to have a minimum of 0.17 m² of retroreflective area facing traffic when used on freeways, expressways, and other high speed highways.

Last Revision Date, 10-10-03

TYPE I BARRICADE

See Note A